TEROS

PART NUMBER
CSS25BKTE1032S

SLIM CASE WITH POWER SUPPLY INCLUDED

TE-1032S

Slim · 10 cm wide · Micro-ATX and Mini-ITX · 250 W SFX power supply

ONLY 10 CM WIDE
Standing or lying flat, with a carry handle

Slim case 10 cm wide with a 250 W SFX power supply already fitted. It stands upright on the included foot or lies flat under the monitor, and has a carry handle, a Kensington slot and a padlock loop. At the front: USB 3.1, USB 2.0, audio and a card reader.



STANDING, LYING FLAT OR UNDER YOUR ARM

REFERENCE IMAGE

WIDTH	POWER SUPPLY	EXTERNAL BAY	SLOTS
10 cm	250 W SFX	5.25"	4 low-profile

WHAT IT SOLVES

A complete PC in ten centimetres of width

10 cm wide

It stands beside the monitor on the included foot or lies underneath, depending on what the desk allows.

250 W SFX power supply

Comes fitted, with a 24-pin main connector, an 8-pin CPU, two SATA and one peripheral connector.

Handle, padlock and Kensington

It lifts with one hand and locks to the furniture with a padlock or cable: built for PCs that move around.

Card reader

The front adds a card reader, and there is an external 5.25" bay for an optical drive.

TEROS

PART NUMBER
CSS25BKTE1032S

The slim format: at 10 cm wide, expansion cards must be low-profile, that is half-height, and the CPU cooler cannot exceed 7.8 cm. Those are the two measurements to check when quoting: the rest of the PC is built as in any other case.

WHERE IT DELIVERS

Built for counters, classrooms and PCs that move

OFFICES AND NEW DESKS

Where every centimetre counts

Ten centimetres wide, standing or flat. It fits in the cash-desk unit, under the monitor or beside the printer.

- 30.6 x 10 x 40.45 cm
- 3.1 kg empty
- Support foot included

CLASSROOMS AND MOBILE PCs

Carry it and lock it

A carry handle to move it between rooms, and a Kensington slot plus padlock loop for when it is left alone.

- Carry handle
- Kensington and padlock
- Card reader

BEFORE YOU BUILD

Which components fit

The slim format sets two conditions: cards must be low-profile and the cooler cannot exceed 7.8 cm in height.

- Low-profile slots
- Cooler up to 7.8 cm
- Mount for one 80 mm fan

DATASHEET · CASE

Structure, power supply and internal capacity

STRUCTURE

Form factor	Slim (SFF)
Supported boards	Micro-ATX · Mini-ITX
Orientation	Vertical or horizontal · support foot included
Expansion slots	4 · low-profile
Colour	Black

MATERIALS AND MEASUREMENTS

Chassis	SPCC / SGCC steel, 0.5 mm
Front panel	ABS plastic
Top panel	Plastic carry handle
Dimensions	30.60 x 10.00 x 40.45 cm (H x W x D)
Net / gross weight	3.10 kg / 3.70 kg

POWER SUPPLY INCLUDED

Format and power	SFX · 250 W
Connectors	1 x 24-pin · 1 x 8-pin · 2 x SATA · 1 x peripheral

STORAGE AND LIMITS

Internal bays	2 x 3.5" · 2 x 2.5"
External bay	1 x 5.25"
CPU cooler	Up to 7.80 cm high
Expansion cards	Low-profile

FRONT, VENTILATION AND SECURITY

Front ports	1 x USB 3.1 · 1 x USB 2.0 · audio · card reader
Button	Power
Ventilation	Top mount for 1 x 80 mm fan
Security	Kensington slot · padlock loop

WARRANTY
12 months
* TEROS products only · new product (NV)

POWER SUPPLY INCLUDED
250 W · SFX
Fitted · 24-pin and 8-pin connectors

COMPATIBILITY
MICRO-ATX · MINI-ITX
4 low-profile slots · cooler up to 7.8 cm

For more information or project advice, contact your authorized distributor.

Images are for reference only. Warranty: 12 months * TEROS products only. TEROS® is a registered trademark.